

09/878,498

01SW102

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions of claims in the application:

Listing of Claims:

1. (Currently Amended) A graphical compare utility system for displaying ~~ladder logic~~ control programs for industrial control modules, the system comprising:
a conversion system operable to receive a first and a second ~~ladder logic~~ control program and convert the first and second ~~ladder logic~~ control program into a first and second data set representing individual instruction of the first and second ~~ladder logic~~ control program; ~~and~~
a viewing system operable to accept the first and second data sets and provide a graphical view of the first and second ~~ladder logic~~ control programs in a single view based on the first and second binary data sets; and
a comparison module operable to maximize individual instruction matches between the first and second control programs.
2. (Currently Amended) The system of claim 1, the graphical utility system providing indicators for insertions, deletions, modifications and moves of individual instructions between the first and the second ~~ladder logic~~ control program.
3. (Cancelled)
4. (Currently Amended) The system of claim 1, the individual instruction being rungs of the first and second ladder logic programs.
5. (Currently Amended) The system of claim 1, further comprising a-difference module operable to determine differences between the first and the second ~~ladder logic~~ control programs and provide a difference data structure representing the differences between the first and second ~~ladder logic~~ control program.

09/878,498

01SW102

6. (Currently Amended) The system of claim 5, ~~further comprising a~~ the comparison module operable to receive the difference data structure and the first and second ~~ladder-logic~~ control programs and generate a plurality of comparison scenarios to provide a plurality of comparison set views.
7. (Original) The system of claim 6, further comprising a decision model operable to determine an optimal display set view from the plurality of comparison set views.
8. (Currently Amended) The system of claim 7, the decision model determining the optimal display set view from the plurality of comparison set views by maximizing individual rung instruction matches between the first and second ~~ladder-logic~~ control programs.
9. (Currently Amended) The system of claim 7, the decision model transmitting the optimal display set view to a viewing component, the viewing component mapping the optimal display set view to graphic components associated with an operating system, such that the optimal display set view can be provided to a display system for providing a graphical representation of the first and second ~~ladder-logic~~ control program in a single view.
10. (Currently Amended) The system of claim 1, further comprising a recursion tool to provide wrapping of the graphical view of the first and second ~~ladder-logic~~ control program, such that instructions of the ~~ladder-logic~~ control programs are wrapped in corresponding panes of a single frame window to avoid clipping of the instructions.
11. (Currently Amended) The system of claim 10, the recursion tool being coupled to window resizing and zooming features of the graphical compare utility system, such that the graphical view of the first and second ~~ladder-logic~~ control programs is dynamically adjusted when at least one of window resizing and zooming is invoked.
12. (Original) The system of claim 10, the recursion tool having an enabled state and a disabled state.

09/878,498

01SW102

13. (Currently Amended) The system of claim 10, the recursion tool being operable to provide a printout of the graphical view of all or a portion of the first and second ladder logic control program.
14. (Currently Amended) A graphical utility system for displaying two control programs for industrial control modules in an adjacent configuration, the system comprising:
- a conversion system operable to receive a first and a second control program and convert the first and second control program into a first and second binary data set representing individual instruction of the first and second control program;
 - a difference module for determining differences between the first and the second binary data set and providing a difference data structure representing the differences between the first and second control programs;
 - a comparison module operable to receive the difference data structure and the first and second control programs and generate a plurality of comparison scenarios to provide a plurality of comparison set views;
 - a decision model operable to determine an optimal display set view from the plurality of comparison set views by maximizing individual instruction matches between the first and second control programs; and
 - a viewing system operable to accept the optimal display set view and provide a graphical view of the first and second control programs in an adjacent configuration.
15. (Previously presented) The system of claim 14, the graphical utility system providing indicators for insertions, deletions, modifications and moves of individual instructions between the first and the second control program.
16. (Cancelled).

09/878,498

01SW102

17. (Previously presented) The system of claim 14, further comprising a recursion tool to provide wrapping of the graphical view of the first and second control programs, such that instructions of the control programs are wrapped in corresponding panes of a single frame window to avoid clipping of the instructions.

18. (Previously presented) The system of claim 17, the recursion tool being coupled to window resizing and zooming features of the graphical compare utility system, such that the graphical view of the first and second control programs are dynamically adjusted when at least one of window resizing and zooming is invoked.

19. (Original) The system of claim 17, the recursion tool having an enabled state and a disabled state.

20. (Previously presented) The system of claim 17, the recursion tool being operable to provide a printout of two side-by-side graphical views of all or a portion of the first and second control program.

21. (Currently Amended) A method for displaying graphical representations of two ladder logic control programs for industrial controllers, the method comprising:

retrieving a first ladder logic control program and a second ladder logic control program;
and

converting the first and second ladder logic control program into a first and second data set representing individual rungs of the first and second ladder logic control program; and

comparing the first and second data sets by maximizing rung matches between the first and second control program; and

providing the first and second data sets to a graphical viewing system, the graphical viewing system being adapted to provide a graphical view of the first and the second ladder logic control programs in a single view.

09/878,498

01SW102

22. (Previously presented) The method of claim 21, further comprising providing indicators for insertions, deletions, modifications and moves of individual rungs between the first and the second ladder logic control program, the indicators being provided in the graphical view.
23. (Cancelled)
24. (Previously presented) The method of claim 21, further comprising determining differences between the first and the second ladder logic control programs and providing a difference data structure representing the differences between the first and second ladder logic control program.
25. (Original) The method of claim 24, further comprising generating a plurality of comparison scenarios based on the differences to provide a plurality of comparison set views and selecting an optimal display set view from the plurality of comparison set views.
26. (Previously presented) The method of claim 25, the selecting of an optimal display set view from the plurality of comparison set views comprising selecting an optimal display set view from the plurality of comparison set views by maximizing individual rung matches between the first and second ladder logic control programs.
27. (Previously presented) The method of claim 26, further comprising transmitting the optimal display set view to a viewing component, the viewing component providing a graphical view of the first and second ladder logic control program in a single frame window.
28. (Previously presented) The method of claim 21, further comprising subjecting the graphical view to a recursive algorithm, such that rungs of the ladder logic control program are wrapped in corresponding window panes of a single frame window to avoid clipping of the rungs.

09/878,498

01SW102

29. (Previously presented) The method of claim 28, further comprising dynamically adjusting the graphical view of the first and second ladder logic control programs in response to at least one of window resizing and window zooming.

30. (Currently Amended) A system for displaying graphical representations of two ladder logic control programs for industrial control modules in an adjacent configuration, the system comprising:

means for converting the first and second ladder logic control program into a first and second data set representing individual ~~runs~~ instructions of the first and second ladder logic control program;

means for determining the differences between the first and second ladder logic control program based on maximizing individual instruction matches between the first and second data sets;

means for determining an optimal display set view based on the differences between the first and second ladder logic control program; and

means for displaying the optimal display set view as a graphical view of the first and second ladder logic control program, the means for displaying the optimal display set view providing indicators in the graphical view representing differences between the first and second ladder logic control program.

31. (Currently Amended) The system of claim 30, further comprising means for wrapping ~~runs~~ instructions in the graphical view of the first and second ladder logic control program.